

REMOTE WATER METER READER

XL NBIOT

DATASHEET



Table of Contents

Table of Contents	2
List of Figures	3
List of Tables	3
Document Release Information	4
1. Description	5
2. Technical Specification	5
3. Remote Water Meter Reader Options	5
4. Features	5
5. Pack Components	6

List of Figures

Figure 1. Remote Water Meter Reader XL NBloT	6
Figure 2. Specialized Waterproof Cable Connectors for Connecting the Remote Water Meter Reader to the Pulse Output of a Water Meter.....	6
Figure 3. Replaceable Industrial Battery Pack.....	6

List of Tables

Table 1: Remote Water Meter Reader XL NBloT Specification	5
Table 2: Remote Water Meter Reader XL NBloT Options	5

Document Release Information

Persons in Charge		Document Information	
Technical Approval	Petar Ivanov	Version	8.1
Authors	Pavel Glavchev, Miroslav Gechev	Release Date	January 2021

1. Description

The Remote Water Meter Reader XL (eXtreme Lifetime) NBIOT is designed to easily connect to standard pulse water meters or other 3rd party equipment, transmit data wirelessly and autonomously utilizing NBloT network protocol, and ensure extremely long battery lifetime.

2. Technical Specification

Parameter	Value
Hardware Version	8.2
Inputs/Outputs	2 digital inputs and 2 digital outputs
	2 analog inputs (max 12V)
	1 Current Loop interface
Operating Temperature	-20 ~ +80°C
Built-in Sensors	Embedded temperature sensor for ambient temperature sensing
Connectivity	NBloT
Power Supply	Industrial battery pack, replaceable (10 years of autonomous work)
Protection Level	IP68, for indoor and outdoor mounting
NBloT Module Certification	FCC/CE
Dimensions	145 x 65 x 55 mm

Table 1: Remote Water Meter Reader XL NBloT Specification

3. Remote Water Meter Reader Options

Product Number	Description
DWM8210DA	NBloT, 2 conductor cable
DWM8210DB	NBloT, 6 conductor cable
DWM8210DC	NBloT, 12 conductor cable

Table 2: Remote Water Meter Reader XL NBloT Options

4. Features

- Pulse registration from standard pulse output water meters, regardless of vendor or pulse volume;
- Equipped with either 2, 6 or 12 conductor cable with a standard length of 1 meter. A pair of two conductors are required to connect to a water meter with a pulse output;
- Easy and quick installation and connection to a pulse output water meter via specialized waterproof cable connectors;
- Remotely configurable data reporting interval (water meter data is read constantly);
- Built-in temperature sensor for ambient temperature tracking and water freeze detection;
- Built-in separate internal helix antenna (not printed on the board) to provide long-distance connectivity and lower power consumption;
- Durable IP68 construction, for indoor and outdoor mounting;
- Replaceable industrial battery pack ensuring long device life. It can be replaced by directly on the field by opening the device's top panel, disconnecting the existing

industrial battery pack, and connecting the replacement. This feature enables the user to protect its investment while not limiting the reporting frequency;

- 10 years average battery life;
- Self-destructive VOID warranty labels for demonstrating external interference or an attempt to violate the integrity of the device;
- Provides effortless multi-platform integration using standard protocols.

5. Pack Components



Figure 1. Remote Water Meter Reader XL NBIoT



Figure 2. Specialized Waterproof Cable Connectors for Connecting the Remote Water Meter Reader to the Pulse Output of a Water Meter



Figure 3. Replaceable Industrial Battery Pack